




**PARTS LIST
ISO 220
ESF Series**

When Ordering Parts
BE SURE TO SPECIFY COMPLETE MODEL NUMBER and SERIAL NUMBER OF REEL
USE PART NUMBER!

Item #	Description	Part #	Qty
02	1" Pipe-Size (1.287" I.D.) Self Aligning Bearing Complete (see ISO-210 for parts)	9902.1400	2
06	Chain, #35	Specify Model	1
12	(25-26) 24.75" Dia. Disc 14 GA - E-Coated (Specify Model & Front/Back)	9903.1321	2
12	(19-20) 18.75" Dia. Disc 14 GA - E-Coated (Specify Model & Front/Back) (not shown)	9903.0821	2
12	(23-24) 22.75" Dia. Disc 14 GA - E-Coated (Specify Model & Front/Back) (not shown)	9903.1121	2
12	(30-31) 28.75" Dia. Disc 14 GA - E-Coated (Specify Model & Front/Back) (not shown)	9903.1621	2
13	Drum, 10-1/2" Dia. 14 GA Steel (Specify Model)	9905.3131	1
19	1-1/2" Rollform Frame Assembly (Specify Model)	Specify Model	1
21	H-26 Ring Gear	9914.0372	1
25A	5/16"-18 x 1/2" Spinlock Bolt (for H-26 Ring Gear and Explosion-Proof Motor)	9904.2158	5 or 9
25B	5/16" x 5/8" Hex Spinlock Bolt (for Non Explosion-Proof Motor)	9904.2159	4
25C	3/8"-16 x 3/4" Spinlock Bolt	9904.2201	10 or 12
25D	3/8"-16 x 1-1/4" Hex Head Cap Screw (for 138T35 Disc Sprocket)	9904.1203	6
25E	1/2"-13 x 1" Hex Head Bolt (for Manual Rewind Assemblies)	9904.1402	2 or 4
27A	3/8"-16 Spinlock Nut	9904.6200	4 or 6
27B	5/16"-18 Hex Head Small Flange Spinlock Nut (for Explosion-Proof Motor)	9904.5100	4
27C	1/2"-13 Hex Spinlock Nut (for Vertical Rewind)	9904.5400	4
28A	1/2" Split Lock Washer (Armor Coat)	9954.0030	2
28B	EH-765 Special Spacer for Disc Sprocket (1" x 5/16" w/ 3/8" Hole)	9954.0017	6
28C	3/8" Flat Washer	9954.0007	4
28D	3/8" Lock Washer, Internal Tooth	9954.0095	6
28E	1" Hub Spacer Washer - Plated (1-7/8" O.D. x 1-5/16" I.D. x 1/8" Thick)	9954.0021	As Req'd.
35	1" Steel Hub Assembly (thru H2M) (Specify Model)	9901.1600	1
42	1" 90 Degree Fx F Steel 4000 PSI Super Swivel Joint (GLT VITON) (HR42-0004)	9929.8552	1
55A	Manual Rewind Assembly w/ H-27	9914.0200	1
55B	VR-2 Vertical Rewind Assembly w/ H-27	9914.0223	1
55C	H-18 Steel Hand Crank - 10" Length (E-Coated) (see ISO-214 for parts)	9914.0011	1
58A	AN-227 12V DC Face Mount 1/3 HP 650 RPM Non Explosion-Proof Motor	9915.0042	1
58B	SX-102 12V DC Base Mount 1/2 HP 650 RPM Explosion-Proof Motor	9915.0013	1
66	ESF Motor Mounting Plate (Right Angle) w/ Hardware (E-Coated) - for "AN" Motors, per P66A-00200 (includes Item 25B)	9923.0015	1
72A	11T35 Motor Sprocket - 1-3/4" Long (Plated) (for Non Explosion-Proof Motor)	9910.1119	1
72B	11T35 Motor Sprocket - 1-1/16" Long (Plated) (for Explosion-Proof Motor)	9910.1117	1
72C	138T35 Disc Sprocket - 16-5/8" Dia. (E-Coated)	9910.1423	1
72C	112T35 Disc Sprocket - 13-3/8" Dia. (E-Coated) (not shown)	9910.1321	1
72C	180T35 Disc Sprocket - 21-3/4" Dia. (E-Coated) (not shown)	9910.1526	1
87	Anodized Aluminum Threaded Spacer Pipe	Specify Model	6